

SPECIFICATION



1.1General Description	3
1.2Features	3
1.3 Application	3
1.4 Package Dimension	4
1.5 Product Parameters	5
1.6 Bin Range Of Luminous Flux and The Chromaticity Diagram (IF=10mA)	BIN
(IF=20mA).....	6
1.7 Typical optical characteristics curves	8
2. Packaging	11
2.1 Packaging Specification	11
2.1.1 Suction box Dimension	11
2.2 Moisture Resistant Packing	12
2.3 Cardboard Box	13
2.4 Reliability Test Items And Conditions	13
2.5 Criteria For Judging Damage	14
3. Handling Precautions	15
3.1 Handling Precautions	15

1. Description


1.1



The White LED which was fabricated using a blue chip and the phosphor LED

1.2 Features

- ▶ Integrated Package.
- ▶ 360 ° Full Angle Luminescence. 360°
- ▶ Suitable for spot welding process.
- ▶ Moisture sensitivity level: Level 5. Level 5
- ▶ RoHS compliant. RoHS
- ▶ Product size: Length* width*thick 134mmX1.7mmX1.9mm




1.3 Application

- ▶ Decorative applications.
- ▶ Other indoor lighting.

1.4 Package Dimension

Fig.1-1 Top view

Fig.1-2 Bottom view



Notes

1. All dimensions units are millimeters.
2. All dimensions tolerances are $\pm 0.5\text{mm}$ unless otherwise noted.

0.5


1.5 Product Parameters

Table 1-1 Electrical / Optical Characteristics at Ts=25°C

Table 1-2 Absolute Maximum Ratings at Ts=

Notes

2. The above forward voltage measurement allowance tolerance is $\pm 1V$.
3. The above color coordinates measurement allowance tolerance is ± 0.005 . ± 0.005 .
4. The above luminous intensity measurement allowance tolerance $\pm 10\%$. $\pm 10\%$.
5. Care is to be taken that power dissipation does not exceed the absolute maximum rating of the product.
6. All measurements were made under the standardized environment of Refond.
7. When the LEDs are in operation the maximum current should be decided after measuring the package temperature. Junction temperature should not exceed the maximum rate. LED
8. ESD yield is over 90% at 2000V ESD (HBM). ESD protection during products handling is needed. 90% LED ESD2000V ,
9. The filament is a non-spectroscopic product, and the commitment batch meets the optical/electrical parameter range of more than 90 %.



1.6 Bin Range Of Luminous Flux and The Chromaticity Diagram (IF=10mA)

BIN (IF=10mA)

Table 1-3

RF-FPR2W2C1K-C5 2200K	Rank250	
	220	280
RF-FPR2W2E1K-C5 2700K	Rank280	
	250	310




Fig 1-3 The C.I.E Chromaticity Diagram CIE

Table 1-4

BIN CODE	CIE-X1	CIE-Y1	CIE-X2	CIE-Y2	CIE-X3	CIE-Y3	CIE-X4	CIE-Y4
22CR	0.4795	0.4111	0.5116	0.4274	0.5264	0.4187	0.4929	0.4033
27E	0.4443	0.4019	0.4615	0.4353	0.4843	0.4407	0.4643	0.4065

1.7 Typical optical characteristics curves




Fig 1-1 Forward Voltage Vs. Forward Current




Fig 1-2 Forward Current Vs. Relative Intensity




Fig 1-3 Central surface temperature Vs Relative Intensity




Fig 1-4 Forward Voltage Vs Central surface temperature




Fig 1-5 Radiation diagram




Fig 1-6 Spectrum Distribution

2. Packaging

2.1 Packaging Specification

SinglePackage:200pcs/box. 200pcs

The whole piece ofPackage:200pcs/box. 200pcs

2.1.1 Suction box Dimension




Fig.2-1 Suction box Dimension

Notes

The tolerances unless mentioned ± 0.1 mm. Unit : mm ± 0.1

2.1.2 Label Form Specification

Table 2-2 Title

P/ N	Part Number
S/N	Spec Number
L/N	Lot Number
Bin Code	Bin Code
Φ	Luminous flux
X/Y	Chromaticity Bin
V_F	Forward Voltage
Ra	Color Rendering Index
QTY	

Fig 2-3 Title

2.2 Moisture Resistant Packing




Fig.2-3Moisture Resistant Packing

2.3 Cardboard Box

Fig.2-4Cardboard Box

2.4 Reliability Test Items And Conditions

Table 2-3 Reliability Test Items And Conditions

TestItems	Ref.Standard	Test Condition	Time	Quantity	Ac/Re /
Thermal Shock	JEITAED-4701 300307	-40 15min ↑↓10s 100 15min	100 cycle	20pcs	0/1
Switching Test	/	25℃, On 2.5min ↑↓ Off 2.5min	2500cycle	20pcs	0/1
Life Test	JESD22-A108	Ta=25 If=10mA	1000hrs	10pcs	0/1
High Temperature High Humidity Life Test	JESD22-A101	60 / 90%RH If=10mA	500hrs	10pcs	0/1

2.5 Criteria For Judging Damage

Table 2-4 Criteria For Judging Damage


Test Items	Symbol	Test Condition	Criteria For Judgement	
			Min.	Max.
Forward Voltage	V_F	$I_F=10mA$	$L.S.L^*) \times 0.90$	$U.S.L^*) \times 1.1$
Luminous Flux	Φ	$I_F=10mA$	No open circuit, shortcircuit or flicke	

Notes

1.U.S.L: Upper standard level

2.

L.S.L: Lower standard level



3. Handling Precautions

3.1 Handling Precautions

(1) LED operating environment and sulfur element composition cannot be over 100PPM in the LED mating usage material. This is provided for informational purposes only and is not a warranty or endorsement. LED LED 100PPM.

(2) In order to prevent external material from getting into the inside of LED, which may cause the malfunction of LED, the single content of Bromine element is required to be less than 900PPM, the single content of Chlorine element is required to be less than 900PPM, the total content of Bromine element and Chlorine element in the external materials of the application products is required to be less than 1500PPM. This is provided for informational purposes only and is not a warranty or endorsement. LED LED 900PPM 900PPM 1500PPM.

(3) VOCs (Volatile organic compounds) emitted from materials used in the construction of fixtures can penetrate silicone encapsulants of LEDs and discolor when exposed to heat and photonic energy. The result can be a significant loss of light output from the fixture. Knowledge of the properties of the materials selected to be used in the construction of fixtures can help prevent these issues. Refond advises against the use of any chemicals or materials that have been found or are suspected to have an adverse affect on device performance or reliability. To verify compatibility, Refond recommends that all chemicals and materials be tested in the specific application and environment for which they are intended to be used. Attaching LEDs, do not use adhesives that outgas organic vapor. LED

LED

LED

LED

(4) Handle the component along the side surface by using forceps or appropriate tools; do not directly touch or Handle the silicone lens surface, it may damage the internal circuitry.



Fig 4-1 Clip filament specification

(5) In designing a circuit, the current through each LED must be exceed the absolute maximum rating specified for each LED. In the meanwhile, resistors for protection should be applied, otherwise slight voltage shift will cause big current change, burn out may happen. The driving circuit must be designed to allow forward voltage only when it is ON or OFF. If the reverse voltage is applied to LED, migration can be generated resulting in LED damage.

LED

LED

(6) Thermal Design is paramount importance because heat generation may result in the Characteristics decline, such as brightness decreased, Color change and so on. Please consider the heat generation of the LEDs when making the system design. LED

LED

(7) Compared to standard encapsulants, silicone is generally softer, and the surface is more likely to attract dust requiring special care during processing. In cases where a minimal level of dirt and dust particles cannot be guaranteed, a suitable cleaning solution must be applied to the surface after the soldering of components. Refond suggests using isopropyl alcohol for cleaning. In case other solvents are used, it must be assured that these solvents do not dissolve the package or resin. Ultrasonic cleaning is not recommended. Ultrasonic cleaning may cause

damage to the LED.

LED

Table 4-1 Storage

Conditions		Temperature	Humidity	Time
Storage 儲存	Before Opening Aluminum Bag	30	75%	Within 1 Year From Date
	After Opening Aluminum Bag	30	60%	24hours 24
Baking		60 ± 5	-	24hours 24

(8) If the moisture absorbent material silica gel has faded away or the LEDs have exceeded the storage time baking treatment should be performed after unpacking and based on the following condition 65±5 for above 24 hours.

60 ± 5 24

If the package is flatulence or damaged, please notify the sales staff to assist.


(9) Similar to most Solid state devices; LEDs are sensitive to Electro-Static Discharge (ESD) and Electrical Over Stress (EOS).

LED

(10) Other points for attention, please refer to our relevant information.

Date

Revisor





Declare

This specification is written both in English and in Chinese and the latter is formal.